

## 37" WXGA LCD-TV

Ver. B



### Feature & Specifications

#### <VIDEO>

- 37" WXGA LCD Display
- CPE (Clear Pix Engine)
- Pixel Resolution WXGA (1366 x 768)
- Response Speed 8 [ms]
- Contrast Ratio 1200 : 1
- Brightness 450 [cd/m2]
- Horizontal Viewing Angle 170[°]
- Vertical Viewing Angle 170[°]
- Picture Control  
(Contrast, Brightness, Color, Tint, Sharpness, Color Temp)
- Sound Control  
(Treble, Bass, Surround, Reset Setting)
- Virtual Surround

#### <TV>

- 181CH. PLL Tuner
- Tuner Auto Set
- MTS/SAP and ATSC Tuner Inside
- Channel Return
- Closed Caption Decoder
- 3D Y/C Comb Filter
- V-Chip(Ver 2.0) Function

#### <CONVENIENCE>

- Trilingual On Screen Display  
(English / Spanish / French)
- Sleep Timer (up to 120 min.)
- All Function Remote Control
- VESA DTC1 Support

#### <INPUT>

- RF Input 1 [set]
- HDMI (Ver 1.0) 2 [set]  
(HDMI / Audio(L/R) + HDMI Input)
- AV Inputs 2 [set]
- Audio Inputs 3 [set]
- S-Video Inputs 2 [set]
- Component Inputs 2 [set]
- PC-IN w/ Audio Mini Jack 1 [set]

#### <OUTPUT>

- Audio Output (L/R) 1 [set]
- Digital Coaxial Out 1 [set]
- Speaker 20(10+10)[W]

#### <WEIGHT & DIMENSIONS>

- Weight: 45.5 [lbs]
- Dimensions (WxDxH): TBD [inch]
- Weight with Packing: 55.7 [lbs]
- Dimensions with Packing (WxDxH): 42.6 x 15.2 x 33.1 [inch]
- Owner's Manual Printed in English & Spanish
- UL Listed, FCC/DHHS Certified
- UPC Code # : 053818640418

#### <CONTAINER LOAD>

- 20ft : 60 units
- 40ft : 132 units
- 40ft-HC : 198 units



High Definition Off Air Reception  
You can enjoy HD Broadcasting Program



HDMI is advanced interface which can receive  
video and audio signals in one cable

\*ALL DESIGN SPECIFICATIONS AND DIMENSIONS ARE TENTATIVE AND SUBJECT TO CHANGE.  
PLEASE CONFIRM SPECIFIC FEATURES AND EXACT SPECIFICATIONS BY REFERENCE TO THE ACTUAL PRODUCT.

[www.sylvaniaconsumerelectronics.com/](http://www.sylvaniaconsumerelectronics.com/)  
[www.funai.us/](http://www.funai.us/)

### FUNAI CORPORATION

201 ROUTE 17 NORTH, SUITE 903  
RUTHERFORD, NJ 07070  
TELEPHONE: 800-966-3862